

TENDER FOR FURNISHING WORK AT SAHAKARNAGAR BRANCH, BENGALURU

SL. No.	DESCRIPTION OF ITEM	QTY	UNIT	RATE in Rs	AMOUNT in Rs
1	BRANCH ENTRANCE PARTITION & CM CABIN PARTITION				
	Providing and fixing in position in Aluminium section 50mm x 50mm 1.5mm thick of JINDAL/ INDAL make as internal frame structure placed horizontally & vertically in 550 mm x 550 mm or 600mm x600mm center to center or as directed by the Architect. The vertical members shall be provided at the junction or every 2100 or 2400 mm or as directed by the Architect or as per the site requirements. The rate shall be inclusive of providing and fixing of 12mm thk toughened glass partition WITH SS PATCH FITTINGS (Make : Ozone/Godrej/Hattich) IN FLOORING & CEILING in position as indicated in the drawings & specifications. Any damage to the newly laid flooring shall be reinstated and complete in all respects. (For Measurement only Installed area will be considered).Note: Rate Including the Stickers & Logo)				
a)	Slid partition above 8' up to ceiling	87.00	Sft		
b)	12mm th. toughened glass partition upto 8' height with 6mm th. SS PATCH FITTINGS (Make : Ozone/Godrej/Hattich) IN FLOORING & CEILING	158.12	Sft		
2	ALUMINIUM FRAMED FULLY PANELLED / PARTLY GLAZED PARTITION				
	Providing and fixing double skin partition using 50mm x 50mm (dimensions) aluminium sections of JINDAL/ INDAL make for frame works with verticals at a maximum spacing of 2 ft. c/c in both directions. The corner verticals shall be common. The partition shall be covered by 6mm MR grade commercial thick plywood on both sides. The finishing shall be with 1mm thick lamination of approved shade on both sides. There shall be a 4" height skirting in the top and bottom on both sides with 1mm lamination finish. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour.Necessary openings for the door shall be provided which shall be finished with beech wood beadings.The lamination shall be provided upto the false ceiling level. payable area shall be for the frame work excluding the door openings .Note: For partly glazed partition, centre panel of the partition above 3 feet to 7 feet level shall be covered with 6 mm thk plain glass instead of plywood and laminate finish. Note Measurement will be taken up to the false ceiling level	500.00	Sft		
3	DOOR FOR PARTITIONS - PARTLY GLAZED				
	Providing and fixing door of size 3' X 7' (W X H) using 30mm thick water proof flush door shutters with around beech wood beading. An opening of 24"x 40" shall be provided. The door shall be finished with 1mm thick lamination of approved shade except for the opening. The opening shall be covered by 8mm thick plain glass fixed with necessary beech wood beadings. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour. All the glass surfaces shall covered on one side as per the design by frosted film of approved make. All the accessories used shall be of concealed type.There shall be 4" height skirting in the bottom with 1mm lamination finish of approved shade . Each door to be fixed to the partition using 5" length stainless steel hinges - 3 Nos and provided with 1 No.of mortice lock, 2 Nos SS handles, 1 No door closure and door stopper of approved make (Godrej/Lakshmi /Aligarh/Doorset) as per Architect or banks incharge	9	No		
4	GLASS DOOR WITH PATCH FITTING				
	Installation of fully glazed frameless glazed door (Single or double leaf of size as mentioned in drawing and as directed by the Architect) made out of 12 mm thk. Toughened glass and the door shall be fixed with Dorma ,Hafele , Hettich or approved make floor springs with SS finish patch fittings on top, bottom. Lock holes in glass for Access control locks, complete in all respect with all hardware, fittings, fixtures etc. complete in all respects. All necessary hardwares, fittings, fixtures to be approved from the Architect or Bank's Officials before actual application of the same. Any change in the specifications must be first approved from the Architect and the Bank.Note: Rate Including the Stickers & Logo				
a	ENTRANCE DOOR & MANAGER CABIN DOORS 3'0" x 7' 0"	2	No		

5	CASH CABIN FRONT & COUNTER TOP PARTITION				
	<p>Providing and fixing partition for cash cabin front by using 50mm x 50mm (dimensions) aluminium sections of JINDAL/ INDAL make for the frame work. There shall be atleast three horizontals at 0'0", 0'8" and 3'6" levels [approx] from the customer counter top level (which will be at 3'6" height from floor level) and two verticals at the ends. The corner verticals shall be common. The exposed surface of wood shall be covered by 6mm thick MR grade commercial grade plywood & finished with 1mm thick lamination of approved shade. The bottom 0'8" height panel to be covered by 7.5 mm thick 56mm x 47mm opening aluminium grill (AL 101) fixed with suitable beach wood corner beadings. At the mid portion of the panel there shall be an opening of 6" x 6" with around wood frame work & this opening shall have a sliding or openable type shutter with locking arrangement from inside to facilitate cash receiving/ paying. The top panel shall be covered by two glass panels made of 12 mm thick plain glass fixed with 8mm thick beech wood beadings of necessary width with an intermediate horizontal gap between two glass panels to facilitate communication between customer and cashier. All the glass surfaces shall covered on one side as per the design by frosted film of approved make. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour.</p>	34.00	SFT		
6	CASH CABIN SIDE & REAR PARTITION				
	<p>Providing and fixing partitions for cash cabin sides & rear areas by using 50mm x 50mm (dimensions) aluminium sections of JINDAL/ INDAL make for the frame work. The verticals spaced at required intervals but not more than 3 feet c/c unless otherwise specified. The corner verticals shall be common. There shall be atleast 4 horizontal wood sections at 0' 0", 2'0", 3'6" and 7'0" levels [approx] from the floor level. The bottom 3'6" height panel to be covered by 6mm thick MR grade commercial plywood on both sides and finished with 1mm thick lamination of approved colour. All the exposed surface of wood sections shall be covered by 6mm thick MR grade commercial grade plywood & finished with 1mm thick lamination of approved shade. The top panel shall be covered by 6mm thick plain glass panels in heights of 250mm with 50mm high slits and fixed with 8mm thick beech wood beadings of necessary width. All the glass surfaces shall covered on one side as per the design by frosted film of approved make. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour. There shall be a horizontal tray at 3 ft level to facilitate slips movement and communication between supervisor and cashier.</p>	70.00	SFT		
7	DOOR FOR BULK CASH CABIN - PARTLY GLAZED				
	<p>Providing and fixing door of size 2'6" X 7' (W X H) using 30mm thick water proof flush door shutters with around beach wood beading. An opening of 18"x 40" shall be provided. The door shall be finished with 1mm thick of approved shade except for the opening. The opening shall be covered by 8mm thick plain glass fixed with necessary beech wood beadings. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour. All the glass surfaces shall covered on one side as per the design by frosted film of approved make. All the accessories used shall be of concealed type. There shall be 4" height skirting in the bottom with 1mm lamination finish. The door shutter shall be fixed with 3 nos stainless steel (SS) make 5" size hinges, one number 6 levered Godrej make (with minimum 3 keys) automatic NIGHT LATCH fixed just below 3 feet level and one 3" long SS material tower bolt and 4" long SS material handles on both the sides.</p>	1	No		

8	ALUMINIUM GRILL FOR BULK CASH COUNTER TOP				
	Providing & fixing 7.5mm thick 48mm X 48mm opening white colour powder coated aluminium grill (AL 101) at the top of the cash cabin fixed with 8mm thick beech wood beadings of necessary width. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour. All the accessories used shall be concealed type. All the aluminium sections shall be white colour powder coated.	82.00	Sft		
9	ALUMINIUM FRAMED PARTLY GLAZED LOW HEIGHT PARTITION				
	Providing and fixing of double skin partition using 5mm x 50mm (dimensions) aluminium sections of JINDAL/ INDAL make for frame works with verticals at a maximum spacing of 2'6" C/C and three horizontals at 0', 2', 3'. The bottom panel upto 3' height shall be covered by 6mm thick MR grade commercial plywood on both sides. The top 1ft panel to be covered by 8mm thick plain glass with exposed top edge and fixed with 8mm thick beech wood beadings of necessary width. The top side of the glass shall be exposed with edges smoothly grided & polished. All the exposed surface of wood sections shall be covered by 6mm thick MR grade commercial grade plywood & finished with 1mm thick lamination of approved colour. All the accessories used shall be of concealed type. There shall be 4" height skirting in the bottom on both sides with 1mm lamination finish. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour. All the glass surfaces shall covered on one side as per the design by frosted film of approved make. Necessary Holes must be made in the frame sections to run the wires, computer cables wherever necessary. Similarly necessary cuttings to be made in the partition to fix switch boxes of electrical, telephone sockets, computer Information outlets etc.	85.00	Sft		
10	FRONT GLASS FOR COUNTER				
	Providing and fixing 12mm thick plain glass of height 10" for the front of the single window counters above the customer top. The vertical supports shall be from the main side partition and fixed with 8mm thick beech wood beadings of necessary width. There shall be 2"/3" gap between the glasses & counter top for easy communication with the customer. The exposed edges of the glass shall be bivelled, grinded and machine finished to render smooth edges. All the exposed wood / wooden beadings shall be neatly finished with 2 coats of wood polish & stained to required colour. All the glass surfaces shall covered on one side as per the design by frosted film of approved make.	53.00	Sft		
11	BULK CASH COUNTER WITH GLASS TOP				
	Providing and fixing Bulk cash counter of following specifications :				
	The counter shall be of length 60"- 72", height 42", working top width of 30", customer top width of 12" with front panel, side vertical support, intermediate support using 19mm thick MR Grade Commercial Plywood. There shall be two draws of size 15" X 22" X 6" (internal dimensions) and one cupboard with shutter at bottom on the right hand side of the counter fixed in between the intermediate support and main support. The draw shall be made of 19mm thick MR Grade Commercial Plywood for all the sides and 6mm MR grade commercial plywood for the bottom. The drawers to be provided with metallic sliding channels with rollers of approved make for easy push and pull. draw bottom Partitions for denomination to be provided using 10mm plywood in first drawer. The working top, customer top, front panel, front face of shutter and draws shall be finished with 1mm thick lamination of approved shade.				

	The customer top & working top shall be provided with 10mm thick plain glass with edges bivelled & polished. A foot rest of size 3" X 1 1/2" hardwood section shall be provided. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm and finished with wood polish. All un exposed surfaces shall finished with 0.8 mm thk laminates. Each draw shall have one multipurpose concealed lock, stainless steel handle and SS hinges for the shutter. Necessary openings for the access of the wires and plugs with wire manager to be provided with PVC caps for the counter top at appropriate location.	1	No		
12	RUNNING LOW COUNTER				
	Providing and fixing Running Low counter of following specifications :				
	Providing and fixing Running customer counter of of different lengths and height 30" and working top width of 30" width (all minimum dimensions) all as per drawing with front, working top, main vertical support upto the working top at every 5ft c/c and intermediate vertical support for draw unit upto working top. The working top shall be at a height of 30". There shall be two drawers of size 13"x 22"x 5" (internal dimensions) fixed in between the intermediate support and main support at every 5ft c/c. The portion below the drawers shall have a cupboard with front shutter. The counter and the drawers shall be made by using 19mm thick MR Grade Commercial Plywood except for draw bottom which shall be provided with 12 mm MR grade commercial plywood.The customer top, working top, customer front & front face of shutter and draw shall be finished with 1 mm thick lamination of approved shade .				
	For every seating area (normally 4'6" to 5 feet length) there shall be a foot rest made of 3" x 2" hardwood section with proper painting finish. The drawers movement shall be with metal sliding channels with rollers. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6mm and neatly polished. The unexposed surfaces except beedings shall be finished 0.8 mm thk laminate of approved make. Each drawer/cupboard shall have one multipurpose concealed lock and 3" long brass or stainless steel handle. Necessary openings for the access of the wires with plug shall be provided with PVC caps with silver tone for the counter top at appropriate location.(any change in the length shall be paid proportionately)	46.00	Rft		
13	TABLES WITH GLASS TOP				
	Providing and fixing Tables of following sizes with front, working top and side vertical support, intermediate vertcal support . There shall be three draws of size 15" X 22" X 5" fixed in alround boxing with top, side vertical, intermediate supports of the table as common side & top. The table & draws shall be made by all by using 19mm thick MR Grade Commerical Plywood except for the draw bottom which shall be with 6mm MR grade commercual ply wood. The draw shall be fixed with metal slider channels with rollers for easy push and pull.The working top, sides, front, front face of draw shall be finished with 1mm thick Lamination. The working top shall be provided with 10mm thick clear glass with edges bivelled and machine finished to render smooth edges. Each draw shall have stainless steel handle with individual locks.				
	A foot rest of 3" X 1 1/2" hardwood section shall be provided. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm and finished with wood polish. All un exposed surfaces shall be provided with 0.8mm thk laminate. Each draw shall have one multipurpose concealed lock, stainless steel handle and SS hinges for the shutter. Necessary openings for the access of the wires and plugs with wire manager to be provided with PVC caps for the counter top at appropriate location.				
	CM Table 3' (W) x 6'6" (L) x 2' 6" (H)	1	No		
	2nd Line Manager 2.5'(W) x 6'(L) x 2'6" (H)	1	No		

14 SIDE CUPBOARD				
Providing and supplying SIDE cupboard of size 3' 6"(L) X 2' 6" (H) X 1' 6" (W) with top, sides, bottom, draws and front swinging shutters all by using 19mm thick MR Grade Commercial Plywood except for the rear portion & draw bottom which shall be covered by 6mm MR grade commercial plywood. There shall be two draws of size 17" X 16" X 5" (all internal dimension). The front, side, rear & top shall be finished with 1mm. The draws shall have sliding arrangement using metal slider channels with rollers for easy push and pull. There shall be skirting of height 3". All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm and finished with wood polish. All un exposed surfaces shall be provided with 0.8 mm Laminate. The swinging shutters shall be fixed using SS hinges. There shall be 4 no.s of SS handles , 3 no.s multipurpose concealed for the entire unit. Any minor variation in the size shall be payable on proportionate volumetric basis.	4	Nos		
15 RUNNING STORAGE CUPBOARDS (SWING SHUTTERS)				
Providing and supplying running storage cupboards of width 18" and height 36" or upto the specified height as per site conditions with top, sides, verticals at every 3ft C/C, horizontal shelves at 1.5 ft C/C or part thereof. The storage unit's verticals, horizontals & front swing shutters all shall be made by using 19mm thick MR Grade Commercial Plywood and only rear side covered by 6 mm Mr grade commercial plywood. The front shutters may be of size 18" to 21" width. There shall be skirting of height 2" to 3". All the visible surfaces like front, top and sides shall be finished with 1mm thick lamination. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm and finished with wood polish. All un exposed surfaces shall be provided with 0.8 mm thk laminate. There shall be one number of multi-purpose lock for every two shutters. Each shutter shall have a stainless steel handle, a brass ball catch/ aluminium powder tower bolt 3" size as the case may be. The payment shall be based on the elevation area of storage units.	174.00	SFT		
16 SHELFs / LEDGES/ FLAP DOORS				
Providing and fixing Shelves/ Ledges/ Flap doors in all horizontal/ vertical surfaces in areas not exceeding 10sqft using 19mm thick MR grade Block board and finished with 1mm lamination on one side. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm and finished with wood polish. All un exposed surfaces shall be finished with 0.8 mm laminate. The Shelves/ Ledges/ Flap doors shall be fixed to the partitions / counters/ cupboards by SS hinges and beach wood beadings for the stoppers.	17.00	Sft		
17 ALUMINIUM FRAMED FULL HEIGHT WALL PANELLING				
Providing & fixing wall panelling using 50mmx 25mm aluminium sections for the frame work spaced at 2 ft ' C/C and clad with 8mm thick MR grade commercial plywood and finished with 1mm thick lamination finish of approved shade. The soffits of the windows shall also be covered with panelling. (Wall panelling shall not be provided behind storages)	1,361.00	Sft		
18 MINERAL FIBRE BOARD GRID TYPE FALSE CEILING ("Silhouette" Type)				
Providing, fabricating, erecting lay-in type tegular/ drop type Mineral fibre board false Ceiling of 600mm x 600mm grid as per the following specifications. The approved brands are ARMSTRONG/ NITTOBO / SAINT GOBAIN with SILHOUTE FINISH, black reveal complete etc., The following specifications are the minimum and tenderers may quote for the equivalent or better specification.	1,274.00	Sft		
The grid system having 600mm x 600 mm or part thereof wherever necessary, shall be made using hot dipped galvanized steel section, exposed surface chemically cleaned capping prefinished in backed polyester paint, main Tee of size 14 x 38 x 0.33mm at every 1200mm c/c max and rotary stitched cross tee of size 14 x 38 x 0.33mm at every 600mm c/c and cross Tee of size 14x 38 x 0.33mm at every 1200 c/c max and 14 x 22 x 0.457mm wall angle around the wall to form grid size of 600 x 600mm. The suspension system shall have 4mm dia pre-straightened GI rods which are in-turn supported from real ceiling using 6mm size anchor bolts, connected with adjustable Hanger clips/ J bolts and other accessories as per the manufacturers specifications. The T Sections have a Galvanizing of 120 grams per M2 & passed through for 500 hrs of Salt test.				
The tiles/ panels shall be of prima Fine Fissured Microlook tegular of ARMSTRONG or Fine Fissured High NRC(Narrow reveal) edge Tiles of Saint Gobain Mineral Fibre Acoustic Ceiling Tiles of size 600 x 600 x 18 mm thick over the formed grid, in module size of 600mm x 600mm x 18mm Thick. with "black Silhouette"				

	The item shall include the cost of additional Tee or L supports & other accessories near the ends/ odd size edges/corners, making necessary openings for electrical light fittings, fire alarm detectors and any other fixtures. No extra payment shall be made for making openings in the panels/ grid for the purpose of light fittings. Item rate shall include all the taxes, transportation, erection, loading & unloading and any other incidental expenditure that may be required to be spent in completing the work in totality as per above specifications. The tiles removed to place light fittings shall be handed over to bank's custody and there may not be any deduction for light fittings area.				
19	GYPBOARD CEILING				
	Providing and fixing suspended false ceiling, which includes providing and fixing GI perimeter channels of size 0.55mm thick having one flange of 20mm and another flange of 30mm and a web of 27mm along with perimeter of ceiling, screw fixed to brick wall/partition with the help of nylon sleeves and screws at 610mm centers. The suspending GI intermediate channel of size 45mm, 0.9mm thick with two flanges of 15mm each from the soffit at 1220mm centers with ceiling angle of width 25mm x 10mm x 0.55mm thick fixed to soffit with GI cleat and steel expansion fastener. Ceiling section of 0.55mm thickness having knurled web of 51.5mm and two flanges of 26mm each with lips of 10.5mm are then fixed to the intermediate channel with the help of connecting clips and in direction perpendicular to the intermediate channel at 457mm centers. 12.5mm tapered edge Gypboard (Conforming to IS- 2095-1982) is then screwed fixed to ceiling section with 25mm dry wall screw at 230mm centers. Screw fixing is done mechanically.	677.00	Sft		
	Finally the boards are to be jointed and finished so as to have a flush look which includes filling as finishing the tapered and square edge of the boards with joining compound, paper tape and two coats of primer suitable for Gypboard (as equivalent) extra frame work for electrical fittings, A/C diffusers, and/or any other cutout, trap doors, wooden shadow battens (hollock wood black enamel painted-25x40mm) at wall peripheries and ends, 12mm thick MDF board for pelmet etc. complete including opening to be made for AC grills, light fittings, trap doors etc. (The quoted rate shall be inclusive of suspenders at all heights) (The rate to be quoted including plastic emulsion paint)				
20	KEY BOARD TRAY WITH MOUSE TRAY				
	Providing and fixing of ready made Key Board tray with Mouse tray of approved make size 20" length (minimum) and 18" (Width) made of metal sheet and finishing with powder coating. The Key board shall be fixed to different items like counters, tables.	12	No		
21	LOGO BOARDS FOR COUNTER ELEVATION				
	Supplying and fixing logo boards on the front laminated surface of counters with 5mm thick acrylic sheet of size 1.5' x 1', attached with SS glass studs (1" or more). Stickers with blue background and bank logo in the center to be pasted on the back side of the acrylic sheet neatly without any bubbles.	12	No		
22	CUSTOMER WRITING DESK.				
	Supplying and fixing free standing customer writing desk of 48" length, 42" height and 18" deep with top, front, side supports and foot rest. There shall be bins of size 6" x 6" (front opening) for keeping challans at the top level, all made out of 19mm thick BWP Block board. The top, front and side surfaces laminated with 1mm lamination. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm. All unexposed surfaces shall be finished with 0.8 mm thk laminate and wood beadings shall be neatly polished with wood polish over a coat of primer. The top shall be provided with 10 mm clear glass edge bevelled fixed with 6 SS studs.	1	No.		
23	SUGGESTION BOX				
	Supplying and fixing Suggestion Box with front opening with door & lock, slot for dropping letters from top, all made out of 12mm MR grade commercial ply wood. The top, front and side surfaces laminated with 1mm thk lamination. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm. All the unexposed area shall be finished with 0.8 mm laminate and wood beadings shall be neatly polished with wood polish over a coat of primer. The overall size shall be 8" x 10" x 12" (D X W X H).	1	No		

24	CHEQUE DROP BOX				
	Supplying and fixing Cheque Drop Box with front opening with door & lock, slot for dropping cheques from top, all made out of 12mm MR grade commercial plywood. The front door shall have 6mm glass 6"x 12" fixed with beach wood beeding. The top, front and side surfaces laminated with 1mm lamination. All the exposed edges shall be provided with beach wood beadings of size 19mm x 6 mm. All the un exposed surfaces shall be finished with 0.8 mm thk laminate and wood beedings shall be neatly polished with wood polish over a coat of primer. The overall size shall be 10" x 12" x 20" (D X W X H)	1	No		
25	NOTICE BOARD				
	Providing and fixing notice board of size 4' X 3' by using 19mm thick Commerical plywood with 1 1/2" X 1/2" beach wood beading alround. The inside surface shall be provided with 12mm thick soft board with fabric on the top. The beach wood eading shall be provided with two coats of polish over a coat of primer.	1	No		
26	GLASS SHELFs				
	Providing and fixing glass panes of required sizes (each shelf not exceding an area of 2 sft) with all edges neatly grinded & polished and fixed to the wall surfaces using D brackets. The glass shall be 12mm thk plain glass of Modi,saint Gobain,asahi make.	10.00	SFT		
27	FLOOR MAT				
	Providing and supplying vinyl mat of size 3ft x 2 ft durotuff make	3	Nos		
28	ROLLER BLINDS				
	Providing and fixing of Luxaflex / MAC make or equivalant brand window ROLLER blinds with top aluminium channel frame with necessary rolling / folding arrangement.	830.00	sft		
29	ATM ENTRANCE PARTITION WITH DOOR				
	a Same as item no.1 a	17.00	Sft		
	b Same as item no.1 b	49.00	sft		
	c Same as item no.4a	1	no.		
30	ATM ROOM - FALSE CEILING				
	SAME AS ITEM 18	24.00	Sft		
	SAME AS ITEM 19	17.00	sft		
31	WALL PANELLING (INTERIOR) (ATM)				
	Providing & fixing wall panelling using 50mm X 25mm aluminium sections for the frame work spaced at 2' C/C and cladded with 8mm thick MR grade plywood and finished with 1mm thick laminat e of approved shade, pasted using Fevicol or equivalent adhesives. The soffits of the windows shall also be covered with panelling.	180.00	Sft		
32	ACP PANELLING (EXTERIOR)				
	Providing and fixing ACP for internal wall cladding using 4mm thk ACP with aluminium foil thickness of 0.50mm on bothsides and 3mmthk poly ethylene core of Euro Bond, Aluco Bond, Aluco panel make. The panel should be of PVDF paint coaing of Bank approved shade and size to withstand for atleast 15years for fading (warranty certificate from the manufactrers is to be given for 15 years against fading, chalking. and delaminations etc) and to be properly fixed to theplywood backing . Plywood backing should be made using 12mm thk MR grade commercial plywoodof centuryply. kitply, uniply make and to be fixed suitably to the masonry wall.ACP should be fixed to the plywood using suitable glue of Dow corning make or equivalent. The rate should include all thematerial, labour,wastage, scaffoldingetc comlete. Payment will be made on sft basis of actual finished area. Note- Combination of various shades should be used as per Bank design wherever Necessary.	500.00	Sft		
33	Painting work: Supply and applying two coats of Tractor Emulsion paint of approved make after making necessary Touchup putty where ever necessary and complete in all respect as per banks requirement.	850.00	sft		

34	PARTLY PLYWOOD PARTITION & PARTY BISON BOARD PARTITION				
	Providing and fixing of double skin partition using 50mm x 50mm (dimensions) aluminium sections of JINDAL/ INDAL make for frame works with verticals at a maximum spacing of 2'6" C/C and three horizontals at 0', 2', 3'. One Side shall be covered by 6mm thick MR grade commercial plywood and finished with 1mm thk laminate and another side Bison Board of 10 mm thk shall be fixed over the frame work and properly finished with painting (two coats) after make necessary joint tapes etc.	773.00	sft		
AMOUNT OF WORK					
GST 18 %					
GRAND TOTAL (incl GST on works contract)					
APPROVED MAKES OF MATERIALS TO BE USED IN THE WORKS					
1	19mm commercial plywood	MAKES: Century Ply, Green Ply, ArchidPly.			
2	12mm commercial plywood	MAKES: Century Ply, Green Ply, , ArchidPly.			
3	8mm commercial plywood	MAKES: Century Ply, Green Ply,ArchidPly.			
4	6mm commercial plywood	MAKES: Century Ply, Green Ply, ArchidPly.			
5	Laminations	Greenlam, Century, Archid, Airolam (Laminate sample to be approved before starting the work)			
6	Prelaminated particle Board	Novopan, Duratuff, Bhutan ,kitlam			
7	Glass	Triveni, Modi, Saint Gobain, ASAHI			
8	Polish	Light house, Sheenlac, Melamine			
9	Adhesive	Fevicol – commercial grade			
10	Teakwood	Well seasoned Indian teakwood, minimum cost to be Rs 1800/- per cft			
11	Hard wood	Well seasoned hardwood, Minimum cost shall be Rs 1200/- per Cft			
12	Aluminium Sections	Jindal, Indal, Hindal			
13	Locks	Godrej or EBCO			
14	Paints	Asian, Nerolac, Berger, Nippon			
15	Cement Bonded Particle board	BISON			
16	Gypsum Board	Gyproc- Saint gobain, India Gypsum			
17	ACP	EURO bond / Aluco bond / Alstrong			
18	metallic sliding channels with rollers	Godrej or EBCO			