

S.NO	DESCRIPTION	UNIT	QTY	Rate (Rs)	Amount(Rs)
	INTERNAL ELECTRICAL WORKS				
	Lights Points(Including Circuit Wiring 2x2.5+1.5 Sqmm)				
	Point Wiring for Light/ Fan/ Exhaust fan with 2runs of 650V grade				
	1.5 Sq.mm FRLS PVC & 1 run of 1.5 Sq.mm PVC insulated				
	Copper wires , run in 25 mm dia heavy gauge PVC conduits				
	concealed in wall / ceiling conforming to IS including all accessories				
	such as junction boxes, conduit bends elbows and ceiling rose,				
	anodised GI Switch box with modular switch and the box covered				
	with front plate.(Point Wiring Include Circuit Wiring From Main Db				
	to SWitch Board with 2x2.5 +1.5 Sqmm Copper fluxible wire etc)				
	One Light point controlled by one 64 gwitch	Noo	35		
а	One Light point controlled by one 6A switch.	Nos	35		
b	Two Lights point controlled by one 6A switch.	Nos	7		
	Expand for point controlled by and switch	Nas	4		
С	Exhaust fan point controlled by one switch.	Nos	4		
d	Ceiling fan point controlled by one switch & Electronic Step type	Nos	3		
	Regulator and Concealed MS fan hook box.				
е	Supply and fixing of 6A, 3Pin Socket outlet switches of 6A rating	Nos			
•	boards for Wall Mounting Fans and (Dependant).				
i	Independent points	Nos	9		
ii	Dependent points	Nos	9		
d	TV. / Inverter points /Bell point	Nos	7		
F 0	Querty and Mising with the following size (COV) mode ED DV()				
	Supply and Wiring with the following size 650V grade FR PVC				
	insulated Copper conductor wires in suitable PVC conduit				
	including end terminations with suitable lugs.				
	a)Supply and wiring of UPS Points wiring from UPS Room DB to	Rmt	86		
	Individual Work Stations With required all Connections and		00		
	Suitable PVC Conduites. 2runs of 2.5Sq.mm PVC wires with 1run				
	of 1.5 Sq.mm PVC Conduite for UPS out going Wirings				
	b) 2runs of 4Sq.mm PVC wires with 1run of 2.5 Sq.mm PVC	Pmt	22		
	Conduite	ixiit	~~~		
	c) 2 runs of 6 Sq.mm PVC wires with 1 run of 4 Sq.mm PVC	Rmt	24		
	insulated Copper earth wire in PVC in conduit. For A/C Sockets				
	d) 2runs of 4.0 Sq.mm PVC wires with 1run of 1.5 Sq.mm PVC	LS	1		
	wire for Name board from the 10 A DP MCB on the main board				
E - 3	Light / Fan Fixtures				

	CANARA BANK AT SOMASWARAM BRANCH,	1		1	
S.NO	DESCRIPTION	UNIT	QTY	Rate (Rs)	Amount(Rs
	Supply and Installation of following type Elypropagat/ Compact				
	Supply and Installation of following type Fluorescent/ Compact fluorescent/ Incandescent light fixtures on wall/ Ceiling including all				
	fixing accesssories such as leads, Teak wood round block etc				
	complete as required. The Fluorescent/CFL fixtures shall be				
	complete with Low loss copper ballast PF improvement capacitor,				
	Bipin Rotor type lamp holder, starter, starter base, all prewired upto				
	the terminal block. All fixtures shall be supplied with lamps. The				
	Catalogue Numbers refers to Philips Make or equivalent approved				
	make .				
	a) Recess mounted LED Luminaire 36 x 1W Class LED, Wipro				
	make code: LM - 036 - XXX - WH - XX.				
	Supply	Nos	16		
	Erection Frame	Nos Nos	16		
	Tame	1103			
	b) Recess mounted LED Down lighter with Pressure die cast				
	aluminium housing (10 x 1W), Wipro make code: LD 49 - 900 - XXX				
	- 60 - XX.				
	Supply	Nos	15		
	Erection	Nos	15		
	c)20W LED Tube light fixture Wall/ Ceiling mounted (Philips				
	Make TMS 200/140)				
	Supply	Nos	10		
	Erection	Nos	10		
E - 4	Ceiling Fans				
	Supply & Eiving of 1200 mm awaan Crompton Make, High Speed				
	Supply & Fixing of 1200 mm sweep Crompton Make High Speed				
	Ceiling fan with standard down rod, all accessories Electrical				
	connections. Including fixing materials required.				
	Supply	Nos	3		
	Erection	Nos	3		
E -5	Wall Mounted Fans				
	Supply & Fixing of 400 mm sweep Wall mounted fan with 3 with				
	metalic body with metalic plates of pin Plug on the lead wire of each				
	fan all accessories Electrical connections. Including fixing				
	materials required.				
	Supply	Nos	9		
	Erection	Nos	9		
E - 6	Exhaust Fans				
	Supply and Installation of heavy duty Exhaust fans with Metallic				
	blades following size sweep with gravity louvres shutters Exhaust				
	fans with Metallic blades of following				
	a) 300mm Sweep(Cromption make Trancent Model)				
		N	<u>^</u>		
	Supply	Nos	3		
	Erection	Nos	3		
E - 7	MAIN DBS / SUB DBS				
		1			

S.NO	DESCRIPTION	UNIT	QTY	Rate (Rs)	Amount(Rs)
5.110			- २८ । ।	1.010 (1.3)	
	Supply Installation Testing and commissioning of TPN MCB Double door Distribution boards dust and vermin protected and rated for 415V, Three Phase AC supply operation including incoming MCB/ELCB as per specifications and required capacity Neutral bar and Earth terminal complete as required and installed in flush with wall including all fixing materials required. MCBs shall conform : 8828 and ELCB /RCCB shall confirm to IS : 12640				
	a)Supply, installation, testing and commissioning of (Double door) with 8Way VTPN MCCB DPX DB with 125A 4Pole MCCB as incomer and 63A TPMCbs -2 Nos, 32A TP MCbs-2 Nos, and 12 nos10/32A SPMCBs s outgoings. (for MAIN DB)	Nos	1		
	b)Supply, installation, testing and commissioning of (Double door) with 4Way TPN MCB DB with 63A 4Pole MCB as incomer and 12 nos10A SPMCBs s outgoings. (for LDB)	Nos	1		
	c)Supply, installation, testing and commissioning of 8way SPN MCB DB (Double door) with 32A DP MCB as incomer and 6nos. 6A/10A/16A SPMCBs as outgoings.(UPS DB)	Nos.	2		
	d)Supply and fixing of 32 A, DP MCB-1No. with encloser for UPS Incoming.	Nos	2		
	e)Supply and fixing of 63A 4 Pole Change over Switch for LDB/UPS Connections with encloser for UPS Incoming.	Nos	1		
E - 8	Raw power Wiring and Sockets: Supply and wiring of Raw Power Points from Main DB to Individual Work Stations With required all Connections with 2runs of 2.5Sq.mm PVC wires with 1run of 1.5 Sq.mm PVC Conduite for UPS out going Wirings and also SAupply and fixing of 1 Nos 6A sockets with 1 Nos 6A switch of modular type with 'front plate and anodised GI box complete 'as required'.for UPS Sockets	Nos	9		
E -9	Supply and fixing of 1no 16A 3pin 'socketswith 16A switch of modular type with 'front plate and anodised GI box complete 'as required'.(Raw Power)	Nos	2		
E - 10	UPS Wiring and Sockets: Supply and wiring of UPS Points from UPS Room DB to Individual Work Stations With required all Connections with 2runs of 2.5Sq.mm PVC wires with 1run of 1.5 Sq.mm PVC Conduite for UPS out going Wirings and also SAupply and fixing of 3 Nos 6A sockets with 2 Nos 6A switch of modular type with 'front plate and anodised GI box complete 'as required'.for UPS Sockets. (UPS -1 conection table / counter no.1,3,5 & 7 and UPS -2 table no. 2,4,6 & 8 etc, and network rack & manager 2 UPS points from UPS-1 & UPS-2.	Nos	11		

S.NO DESCRIPTION UNIT QTY Rate (Rs) Amount(f E Supply and fixing of 3 Nos 16A sockets with 1 Nos 16A switch of Nos 2 required for UPS Sockets 2 2 2 E 12 Supply installation testing and commissioning of AC Units With 2004 With 2502A SP MCB set(Like Metal Clad Socket With 1502A Stabilizer to AC Units) Nos 7 E - Supply and erecting of approved make telephone RJ 11Jack for Nos Table phone with 2 pair .5mm Thick Telephone cable including pvc conduite with required all materials From Outside to Rack locations Nos 1 E - Supply and Laying of 10 pair .5mm Thick Telephone cable including pvc conduite with required all connectors box with 10 Pair 15 connectors and required all contectors box with 10 Pair 15 connectors and required all contectors box with 10 Pair 16 connectors and required all contectors. Nos 1 E - 16 MV Cables Import the required all contectors box with 10 Pair 16 contector materials When the cable to be latid in ground, the same shall be laid at depth of 750mm below ground level including excavation and refiling of earth after cables are laid, providing protection with sand and bricks at sides and the prings. The cable shall contor to 15 1554/ Part LCable protected in 2* Dia Cable route markers at every 15mt. Interval and also the turnings. The cable shall contor to 15 4554/ Part LCable protected in 2* Dia Cable route markers at every 15mt. Interval and also including end termination and Earthing of Gland with 85WG 'Gl Wire<		CANARA BANK AT SOMASWARAM BRANCH ,				
11 modular type with 'front plate and anodised Gi box complete 'as Image: Complex	S.NO	DESCRIPTION	UNIT	QTY	Rate (Rs)	Amount(Rs)
2x43cgmm+2.5Sgmm Copper Fluxible Wire From Main DB to AC Units including Legrand Make 20A Metal Clad Socket with 25/32A SP MCB set(Like Metal Clad Socket+Wiring From Db to AC Box to Stabilizer to AC Units) E - Supply and erecting of approved make telephone RJ 11Jack for 13 telephone with 2 pair. 5mm Thick Telephone cable including pvc conduite with required all materials (RJ-11 Jack+2 pair Cable) Nos 7 E - Supply and Laying of 10 pair Smm Thick Telephone cable 14 including pvc conduite with required all materials From Outside to Rack locations Mts. 68 E - Supply and fixing of 10 pair Crone Connector box with 10 Pair 15 connectors and required all connections. Nos 1 E - H MV Cables Image: Stabilizer to AC Units Supply, laying and commissioning of following size 1.1KVgrade PVC insulated armoured aluminium conductor underground cable, in built up cable trench/2" PVC pipe or on cable tray with all installation materials.When the cable is to be laid in ground, the same shall be laid a depth of 750mm Below ground level including excavation and refilling of earth after cables are laid, providing protection with sand and bricks as ides and topand cable route markers at every 15mt: interval and also atthe turnings. The cable shall conform to IS 1554/ Part I.Cable protected in 2" Dia G. I Pipe10' long at the pole (corret measurement should be taken by the contractor before procuring the cable. Rmt 72 E-17 Providing Indoor ordinary end terminations for the cable specified above with compression type steel gland, Bi-metallic lugs using crimping tool, insulation tape, identification tage set, including end termination and Earthing of Gland with 8SWG 'Gl Wire No <td></td> <td>modular type with 'front plate and anodised GI box complete 'as</td> <td>Nos</td> <td>2</td> <td></td> <td></td>		modular type with 'front plate and anodised GI box complete 'as	Nos	2		
13 telephone with 2 pair .5mm Thick Telephone cable including pvc conduite with required all materials (RJ-11 Jack+ 2 pair Cable) Image: Cable State	E -12	2x4Sqmm+2.5Sqmm Copper Fluxible Wire From Main DB to AC Units including Legrand Make 20A Metal Clad Socket with 25/32A SP MCB set(Like Metal Clad Socket+Wiring From Db to AC Box to	No	4		
14 including pvc conduite with required all materials From Outside to Rack locations E Supply and fixing of 10 pair Crone Connector box with 10 Pair Nos 1 E Supply and fixing of 10 pair Crone Connector box with 10 Pair Nos 1 E MV Cables 1 E Supply, laying and commissioning of following size 1.1KVgrade PVC insulated armoured aluminium conductor underground cable, in built up cable trench/ 2" PVC pipe on cable tray with all installation materials. When the cable is to be laid in ground, the same shall be laid at a depth of 750mm below ground level including excavation and refilling of earth after cables are laid, providing protection with sand and bricks at sides and topand cable route markers at 'every 15mtr'. Interval and also atthe turnings. The cable shall conform to IS 1554/ Part I.Cable protected in 2" Dia G.I Pipe10' long at the pole (correct measurement should be taken by the contractor before procuring the cable. Rmt 72 E-17 Providing Indoor ordinary end terminations for the cable specified above with compression type steel gland, Bi-metallic lugs using crimping tool, Insulation tape, Identification tags etc., including end termination and Earthing of Gland with 8SWG 'GI Wire No 2 a) 3.5C X 50 Sq.mm No 2 1		telephone with 2 pair .5mm Thick Telephone cable including pvc	Nos	7		
15 connectors and required all connections. Image: Connectors and required all connections. E -16 MV Cables Image: Connectors and required all connections. B -16 MV Cables Image: Connectors and required all connections. Supply, laying and commissioning of following size 1.1KVgrade PVC insulated armoured aluminium conductor underground cable, in built up cable trench/2" PVC pipe or on cable tray with all installation materials.When the cable is to be laid in ground, the same shall be laid at a depth of 750mm below ground level including excavation and refilling of earth after cables are laid, providing protection with sand and bricks at sides and topand cable route markers at 'every 15mtr. interval and also atthe turnings. The cable shall conform to IS 1554/ Part I.Cable protected in 2" Dia G.I. Pipe10' long at the pole (correct measurement should be taken by the contractor before procuring the cable. Rmt 72 a) 3.5C X 50 Sq.mm Rmt 72 Image: Connector and Ferminations for the cable specified above with compression type steel gland, Bi-metallic lugs using crimping tool, Insulation tape, Identification tags etc., including end termination and Earthing of Gland with 8SWG 'GI Wire Image: Connector Procure		including pvc conduite with required all materials From Outside to	Mts.	68		
Supply, laying and commissioning of following size 1.1KVgrade Image: Communication of the second stress of the			Nos	1		
above with compression type steel gland, Bi-metallic lugs using crimping tool,Insulation tape,Identification tags etc., including end termination and Earthing of Gland with 8SWG 'GI Wire Image: Comparison of		Supply, laying and commissioning of following size 1.1KVgrade PVC insulated armoured aluminium conductor underground cable, in built up cable trench/ 2" PVC pipe or on cable tray with all installation materials.When the cable is to be laid in ground, the same shall be laid at a depth of 750mm below ground level including excavation and refilling of earth after cables are laid,providing protection with sand and bricks at sides and topand cable route markers at 'every 15mtr. interval and also atthe turnings. The cable shall conform to IS 1554/ Part I.Cable protected in 2" Dia G.I Pipe10' long at the pole (correct measurement should be taken by the contractor before procuring the cable.	Rmt	72		
E -18 Earthing a) Providing G.I. Earth station, with 40mm dia 2500mm longGl pipe including construction of brick pedestal, providing meshed funnel,Cl cover and other civil Engineering works,spreading a homogenous mixture of salt, charcoal aroundthe pipe etc, completely as per IS No 1	E-17	above with compression type steel gland, Bi-metallic lugs using crimping tool,Insulation tape,Identification tags etc., including end termination and Earthing of Gland with 8SWG 'GI Wire				
a) Providing G.I. Earth station, with 40mm dia 2500mm longGl pipe No 1 including construction of brick pedestal, providing meshed funnel,Cl cover and other civil Engineering works,spreading a homogenous mixture of salt, charcoal aroundthe pipe etc, completely as per IS		a) 3.5C X 50 Sq.mm	No	2		
including construction of brick pedestal, providing meshed funnel,CI cover and other civil Engineering works,spreading a homogenous mixture of salt, charcoal aroundthe pipe etc, completely as per IS	E -18	Earthing				
		including construction of brick pedestal, providing meshed funnel,CI cover and other civil Engineering works,spreading a homogenous mixture of salt, charcoal aroundthe pipe etc, completely as per IS	No	1		

	CANARA BANK AT SOMASWARAM BRANCH ,			LIECUIC	al works	
S.NO	DESCRIPTION	UNIT	QTY	Rate (Rs)	Amount(Rs)	
	b) Providing Copper Earth station, with 600X600X3.15mm Copper plate at 2500mm depth including construction of brick pedestal, providing meshed funnel,CI cover and other civil Engineering		1			
	works, spreading a homogenous mixture of salt,charcoal around the pipe etc,completely as per IS3043,1987 or latest revision.					
	c) Supply and laying of following size strips including including all necessary inter connections with earth station and equipments.					
	i) 8 SWG Copper wire	Rmt	48			
19 a	LAN Cable Supply and Laying of 4Pair CAT-6E LAN Cable with suitable PVC					
	Conduite and Junction boxes with etc.	Pts	16			
b	Supply and fixing of CAT-6E Information out letsSystimax/ Amps/ D Link	Set	16			
С	Supply of Patch Cards 3' (Factory Crimping)	Set	16			
d	Supply of Patch Cards 7' (Factory Crimping)	Set	16			
е	Supply and fixing of 24 port Jack panel (Systimax/ amp)	Set	1			
f	Supply and fixing of 9U Rack encloser with accries likeSelf Power manager, Cable Manager, Hard Ware etc.	Set	1			
g	Supply and fixing of 24 ports d-link switch	Set	1			
20	Dismentalling of old wiring & Providing Temporary Connections at the time of Renovations Period.	LS	1			
Α	TOTAL AMOUNT FOR BRANCH ELECTRICAL WORKS Rs :					
	GST EXTRA		18%			
	Rupees					