

BOQ OF INTERIOR FURNISHING WORK FOR CANARA BANK, SHEOGANJ BRANCH, UDAIPUR					
S.No.	ITEM	QTY.	UNIT	RATE	AMOUNT
1	LAMINATED / GLAZED PARTITION providing fabricating & fixing of partition made out with unanodised aluminium Framework consisting of 2"x1" Section placed at min 2'x2' horizontally & vertically (as per site requirement) with 8 mm thick water proof Ply finished with 1mm thick approved laminates (of approved shade) on both sides. The exposed sides / top shall be finished with teak wood beading (3" x 1") with melamine polish / approved shade / natural polish . This partition will be either Low Height upto 3' ht. with wooden pattern & above 3' height 18" ht.12mm thick toughened clear glass / aqua blue shade (approved make) or Full Height Partition. Antitermite paint will must before fixing any ply. Height upto False Ceiling Height only be considered for payment.	440	sqft		
2	COLUMN / WALL PANELLING Providing & fabricating of column / wall panelling made out with un-anodised aluminium Framework consisting of 1" x 1" pipe placed at min. 2'x2' horizontally & vertically (as per site requirement) with 8 mm water proof Ply finished with 1mm thick approved laminates (of approved shade) . The exposed sides / top shall be finished with teak wood beading (3" x 1") with melamine polish / approved shade / natural polish on all column & walls as per approved drawings. The rates are including the design provided in the approved drawing .Antitermite paint will must before fixing any ply.	765	sqft		
3	WOODEN DOOR Providing and fixing flush door with 1 mm. laminate on both side . The item including providing and fixing 75 x 50 mm. dark brown teak wood choukhat . The edges of door to have 12 mm. teak wood lipping finished with malamine polish , fixing 10 mm. thk glass with tw beading . the 3 LEAVER lock (godrej) ,s.s. handles , hinges , stoppers , door closer of approved make etc. completed in all respect.	74	sqft		
4	CUPBOARD (Low Height/full height) Providing & fixing 450 mm deep cupboards/ storage units with sides, Top, bottom, shutters,partitions & shelves made of 19 mm thick commercial board conforming to IS 303 of approved quality and make. The partitions shall be spaced at a maximum spacing of 810 mm C/C and shelves shall be spaced at 450mm C/C The width of each shutter shall not exceed 450mm. The back shall be made of 9 mm comm. ply conforming to IS 303 with 1 mm approved laminate. The front shutter and exposed sides shall be finished with approved laminate (in two shades as per design) of approved quality & shade as per design with groove . The exposed edges of the board shall have teak wood lipping finished with melamine polish . Skirting shall be 100mm high & made of 19mm thick IS 303 commercial board finished with 1mm approved laminate. Top of cupboard will finished with 1mm thk approved laminate The rate includes necessary s.s. hardware such as self close telescopic hinges, tower bolts, brass dead locks,magnet catchers, 4" long aluminium handle of approved design. All fixtures shall be S.S. only. All inner surfaces shall be laminated with .8 mm white laminate. All exposed teak surfaces shall be finished with teak wood melemine polish.	110	sqft		
5	FALSE CEILING (Gypsum Board) Providing & fixing false ceiling as per design consist of GI frame, which includes perimeter channels alongwith the parameter of ceiling, with intermediate channel of size 45mmx0.9mm thick with two flange of 15mm each @ 1220mm c/c with ceiling angle of size 25x10x0.5mm fixed to the bottom of the ceiling with GI cleat & steel expansion fastener, ceiling section of 0.55mm thick with knurled web of 51.5mm & two flanges of 26mm each with lips of 10.5mm are then fixed to the intermediate channel with connecting clips				

	and direction perpendicular to the intermediate channel at 457mm c/c , 12.5mm thick gypsum board shall be fixed with screw with filling & finishing the tapered edge with jointing compound, paper tape and painted with two or more coats of plastic emulsion paint over a coat of primer.The item includes P/F perimeter channel of size 20x27x30mm and 0.55mm thick for light fittings, AC grills,diffusers & for light fixtures, A.C. etc. with 40x40mm teak with 40x40mm TW moulding all around, around the walls / pillars All complete as per design. (The finished surface area shall be measured) height of ceiling is 12' approx. it will use 1" x 2" holo iron section in both ways @ 10' c/c welded frame for supporting the false ceiling structure .	480	sqft		
6	FALSE CEILING -GRID				
	Providing & fixing Grid false ceiling (armstrong or equalvent company product) with 12mm thick mineral fibre acoustic tiles with crisp finely granulated surface in bright colour Prima regular Fine Fissured RH 99 with Arm strong TL 24mm exposed grid Tee section, exposed face shall be powder coated (white), main runner shall be Tee-shape section with single rotary stitching of size 24x38mm , 3.6m long with cross runner of tee shape section with single rotary stitching of size 24x30mm @1.2m with 24x25mm runner @ 0.60m c/c, with Armstrong suspenders, perimeter channel of size 22x22mm (white) all complete in all respect as per manufacturer's specifications.	434	sqft		
7	12 MM TH. TOUGHENED GLASS Door				
	12 MM TH. TOUGHENED GLASS Cabin door providing & fixing main doors/cabin made out of/cabin door made out of HNG/ Asahi India /saint gobin MAKE 12 MM TH.toughened plain glass in single piece with computrised diamond cut & diamond edge polish including making required cutout holes for lock , handles , pivot patch fitting , corner fitting hinges etc. the rate is inclusive of patch fitting of dorma / ozone make floor spring ,pivot patch fitting with cover plate locks handles, frost film , signages with necessary hardware rtc. as per intructions of Architect/Engineer.	49	sqft		
8	12 MM TH. TOUGHENED GLASS FIXED SECTION				
	FULLY GLAZED 12 MM TH. TOUGHENED GLASS PARTITIONAs above item no 1 Aa (both side gyp.board finished partition but partition shall have 12 mm th. Toughened plane glass fixed with 1 1/2" x 1" teak wood moulding finished with melamine polish with stainless steel "D" Brackets, frost film etc . Complete as per detailed drawing & innstuction of Architect /Engineer .	177	sqft		
9	TABLES				
	Providing TABLES in position with Writing top, sides & front apron all be made of 19mm thick IS 303 commercial board (APPROVED MAKE) with teak wood lipping on all exposed ends of Ply board. The front apron & sides shall be finished with 1mm thick approved laminate of approved shade. The writing top shall be provided with 1mm thick approved laminate of approved quality and shade with teak wood edging all around.The skirting shall be 100mm high finished with 1mm thick approved laminate of approved shade. There shall be wooden foot rest made of hollock wood .There shall be key board tray made of 19mm IS 303 block board with teakwood lipping and approved make sliding fittings. All inner surfaces of table surfaces shall be finished with .8 mm white laminate.				
A	1800mm x 900mm x 750mm high with drawer unit consists of 1 drawers, mounted on telescopic sliding channels & one open self fixed with telescopic hinges. All made of 19 mm IS303 block board and 1 mm. approved lamination finish.	1	nos		
B	1575 mm x 750 mmx 750mm high with drawer unit consists of 1 drawers, mounted on telescopic sliding channels & one open self fixed with telescopic hinges. All made of 19 mm IS303 block board and 1 mm. approved lamination finish. 12 mm toughened glass partation will fixed on front of counter top (above 750 mm) fixed with D - brackets / polished wooden battens . the height of glass is 600 mm for normal counters no extra work is included in counter.	1	nos		

C	1350mm /1350 mm x 750 mmx 750mm high with drawer unit consists of 1 drawers, mounted on telescopic sliding channels & one open self fixed with telescopic hinges. All made of 19 mm IS303 block board and 1 mm. approved lamination finish. 12 mm toughened glass partation will fixed on front of counter top (above 750 mm) fixed with D - brackets / polished wooden battens . the height of glass is 600 mm for normal counters & no extra work is included in counter.	2	nos		
10	CASH COUNTER				
	Providing & fixing cash Counter as per layout plan with two writing top, one writing top for caisher at 750 mm and another writing top for customer at 1350 mm with two intermediate support @ 1500mm / 1350 mm as required & front apron writing top, sides all made of 19mm thick comm. board (approved make). The front apron, writing top exposed sides, shall be finished with 1mm thick approved laminate of approved shade. All the exposed edges shall be finished with teak wood lipping malimine polish.The skirting shall be 100mm high with 1mm thick approved laminate. There shall be a CPU shelf @ 1500 mm of size 600 x 300mm made of 19mm comm. board fixed at height of 150mm inside the counter with alround teakwood lipping . There shall be wood foot rest made of hollock wood. There shall be key board tray @ 1500 mm made of 199mm comm. board with teak wood lipping and ebco make sliding fittings. There shall be a three draw unit @ 1500mm.	5.25	RFT		
	The size of each drawer shall be 15"x22"x5" (all internal dimensions) The unit shall made within the intermediate/side supports. The drawers shall be made of 19mm commercial block board .The drawer bottom & rear of the unit made of 6mm thick IS 303 ply. The front face of the draw shall be covered by 1mm approved lamination of approved shade and make. The draws shall be fixed with readymade telescopic metallic sliding channel. Each drawer shall have multipurpose lock and aluminium handle. All fixtures shall be powder coated. All the inner surfaces shall be finished with .8 mm laminate of approved make . The overall dimensions shall be : Width of top = 750 mm, height of platform= 750mm. 12 mm toughened glass partation will fixed on front of counter top (above 750 mm) fixed with D - brackets / polished wooden battens . the height of glass is 600 mm for normal counters and 1200 mm for cash cabin front. no extra work is included in counter.				
11	CUSTOMER WRITING STAND				
	Providing in position writing stand,The structure shall be made of 19mm thick comm. board around column with 1.0mm thick approved laminate, shelf finished with 1mm approved laminate with 12mm thick beveled edge glass upper top in required shape, with 75mm high 12 mm thick skirting exposed surfaces shall be stained to approved colour finished with melamine polish.all inner surface will finished with .8 mm laminate.	1	each		
12	Providing & fixing aluminum alloy concealed type door closer (ISI approved make, everite door king)	2	nos		
13	A.C.P. PANELLING				
	Providing & fixing full height interior grade A.C.P. wall paneling 4 mm thick in two or more shades/ design fixed on 50 X 25 Aluminum frame at 600 centre to centre both sides horizontal & vertical. The paneling to be finished with silicon complete in all respects as per Bank/ Architect.	135	sqft		
14	3M Frosted Film				
	Providing & fixing in position '3M' make frosted glass film in stardust range fixed to glass as per pattern. Area of application to be measured as maximum length x maximum height of application on that particular piece of glass.	80	sqft		
15	NOTICE BOARD				
A	Notice Board -600 X 1200 MM	1	nos		
B	Notice board - 600 x 457 mm	1	nos		
16	OBD PAINT				
	P/f Asian or approved make royal play texture paint of approved design and shade.	200	sqft		
	Total				

Seal & Sign of Tenderer